





# UKCA Full Quality Assurance Certificate

This is to certify that:

Andronaco Industries 4855 Broadmoor Ave Kentwood Michigan 49512 USA

Holds Certificate Number:

UKCA 768591

In respect of:

#### **Pressure Accessories**

On the basis of our examination under the requirements of the Pressure Equipment (Safety) Regulations (SI 2016/1105) as amended by the Product Safety and Metrology etc (Amendment etc)(EU Exit) Regulations 2020 (SI 2020/676) for Conformity Assessment Procedure Module H - Conformity based on full quality assurance.

For and on behalf of BSI, an Approved Body for the above Regulation (Approved Body Number 0086):

Frank Lee, Product Certification Technical and Compliance Director

First Issued: 2022-05-25 Latest Issue: 2022-06-06 Effective Date: 2022-06-06 Expiry Date: 2025-05-31

Page: 1 of 2

## ...making excellence a habit."

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request. To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated <u>online</u>.

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK. A member of BSI Group of Companies.

### UKCA Full Quality Assurance Certificate

No. UKCA 768591

#### **Additional Information**

### **Limitations of Certificate Validity**

Design, manufacture, inspection and test of the product ranges listed below: -Pureflex, Inc – Chemical Resistant Hose, Fibre Reinforced Composite Valves and Composite Piping/Fittings Size Range = DN32 (1.25"NB) to DN900 (36"NB) Maximum allowable pressure, PS = up to 20 bar (290 psi)

> Nil-Cor, Llc – Fibre Reinforced Composite Valves Size Range = DN32 (1.25"NB) to DN900 (36"NB) Maximum allowable pressure, PS = up to 20 bar (290 psi)

Ethylene, Llc – "T-Line Strainers"<sup>™</sup>, "Flexi-Joint"<sup>®</sup> PTFE Expansion Joints and "Flo-Vu"<sup>®</sup> Sight Flow Indicators Size Range = DN32 (1.25"NB) to DN1050 (42"NB) Maximum allowable pressure, PS = up to 14 bar (203 psi)

Hills-McCanna, Llc – Metallic/Non-Metallic, Lined/Unlined Diaphragm, Ball, Butterfly and Plug Valves Size Range = DN32 (1.25"NB) to DN300 (12"NB) Maximum allowable pressure, PS = up to 17.24 bar (250 psi)

First Issued: 2022-05-25 Latest Issue: 2022-06-06 Effective Date: 2022-06-06 Expiry Date: 2025-05-31

Page: 2 of 2

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request. To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated <u>online</u>.

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK. A member of BSI Group of Companies.